

CUTTING MACHINE MOD. C42 3-PHASE



Measures : cm. 118 x 71 x h. 87

Weight : Kg. 605,00

Oil : Kg. 4,00

Electric Motor : 4 HP / 3 KW

Rpm : 90

| Cutting capability | R. = 65 Kg. / mm ² | | | R. = 85 Kg. / mm ² | | |
|--------------------|-------------------------------|--------|--------|-------------------------------|--------|--------|
| | 1 Ø 34 | 2 Ø 26 | 3 Ø 20 | 1 Ø 30 | 2 Ø 20 | 3 Ø 16 |

- Gears and pinions in special hardened steel operate in constant oil-bath inside a sturdy structure in heavy laminate.
- The innovative **Bar Slider Roll** ensures easier rod movement towards the blade.

STANDARD EQUIPMENT

1 set composed of two blades, already fitted on the machine.

OPTIONALS

Lubrication Pump



Special manual pump with flow adjuster, for constant and easy lubrication of all the parts liable to seizure. It is easy to use. Simply press the batching cylinder control knob once a day, in case of daily and regular use of the cutting machine.

Screw Locator



Adjustable according to the diameter and quantity of bars to be cut, permits perfect alignment of one or more rods towards the blade and the achievement of perfectly perpendicular cuts.